



Specifications:

Model 2000VR Maximum Privacy - 70"

Plastic Laminate Toilet Partitions

Materials:

- Materials shall be as manufactured by Buddsteel Architectural Products Limited at 519-392-6060.
- Design: Partitions shall be floor mounted and overhead braced.

Fabrication:

- Panels, pilasters and doors shall be 1" thick, fabricated using an industrial grade sanded particleboard core, covered with high-pressure decorative laminate sheets. Partitions shall receive a matching plastic laminate edge. Colour selection shall be chosen from the standard laminate range.. Standard doors shall be 24" wide and barrier free doors shall be 36" wide unless specified otherwise. Panels and doors shall be 58" high. Pilasters shall be 82" high.

Hardware: Heavy Duty Anodized Aluminum – Through Bolted For Maximum Strength

Door hardware and brackets shall be manufactured from anodized aluminum heat treated to a T-5 condition, fabricated from 6063-aluminum alloy with continuous stainless steel hinges.

- **Hinges:** Continuous hinges shall be pre-adjusted to leave in-swinging doors approximately 6" open and out-swinging doors closed when not in use.
- **Coat Hook:** One coat hook with a protective rubber bumper end shall be installed per unit.
- **Door Stop:** Each door shall receive one full height heavy duty door bumper for a gap free sightline.
- **Wall Brackets:** All panels and pilasters shall be secured with full height continuous U-shaped wall brackets. Brackets will be through bolted to the partition material with vandal resistant one-way fasteners.
- **Slide Latch & Keeper:** Each door shall receive a slide latch and keeper. The slide latch shall be fastened with two through bolts and allow for emergency access for both in and out swing doors.
- **Shoe:** A 3" high, U-shaped aluminum shoe shall be secured to the floor and partition material. End caps shall be mechanically fastened to finish each open end.

Overhead Brace: The anodized aluminum overhead rail bracing shall be mounted approximately 83" off the floor and will be of an anti-grip design. Partition inserts shall be secured above all doors, inside this rail to ensure no movement.

Installation:

- Partitions shall be installed secure, plumb and square.
- A maximum of a 1/2" space shall be allowed at all wall and panel or end pilaster areas.
- Brackets shall be securely fastened to walls with anchors and screws.
- Adjust and align hardware for easy and proper function ensuring doors swing free.
- All areas shall be left in a neat and tidy state upon completion.

Vandal Resistant & Privacy Options Included:


- Continuous 69" High Alum Brackets
- Continuous 69" High Stainless Steel Hinges
- Continuous 69" High Door Stops



ELEVATIONS



Model 2000VR Maximum Privacy



PRIVACY HARDWARE



Continuous Hinges




Continuous Door Bumper



Slide Latch & In Swing Keeper



Coat Hook



Continuous Brackets



* MOST POPULAR COLOURS*

Pearl
Soapstone
Stocked &
Readily Available

Grey
Glaze

Pebble
Piazza

Almond
Leather

Silicon
Ev

Tungsten
Ev

White
Tegris

Handspun
Dove

Grey
Pampas

Titanium
Ev

Pewter
Mesh

Kingswood
Walnut

Pewter
Brush